

# Wave Soldering System

A/T/F

ATF 13/25

Lead-free ready



## System:

- Belt-driven pallet conveyor
- Stainless steel foam fluxer
- Microprocessor controlled
- IR-preheater, with Ceran glass cover
- PID control
- Lead-free ready solder pot, with removable flow ducts
- Dual wave, with direct driven solder pumps
- Wave intermittent operation
- Meets VDE safety regulations

## Options:

- Pumpless spray fluxer
- Integrated filter above spray fluxer
- Convection preheater
- Insulated tunnel above preheater
- Nitrogen inerting
- Pin code reader
- Interchangeable solder pot
- Bench, with or without panels and doors
- PC-software
- Assembly conveyor systems

# Description Wave Soldering System ATF 13/25



## System

- Sturdy steel base frame
- All modules designed for easy maintenance

- Rigid hoods include antistatic safety glass allow full monitoring of working process
- 2 exhaust ducts (above fluxer and solder pot)
- o Bench, with or without panels and doors



## Fluxer module

- Foam fluxer fitted as standard
- Whole unit is adjustable in height
- Air regulator pressure gauge and flow control valve


- o Spray fluxer



## Preheat module

- High efficiency IR preheater
- Fine adjustment of temperature
- Ceran glass cover for easy cleaning

- All values shown at digital display
- o Convection



## Solder pot ready for Lead-free

- Stainless steel solder pot with ceramic coating
- Quick-lock solder pumps
- Pot installed with direct driven pumps (24V DC motors)
- Removable flow ducts and nozzles

- Solder temperature shown at digital display
- o Interchangeable solder pot



## Solder wave

- Special designed solder flow decreases production of dross
- Separate Microprocessor controlled wave heights

- Dual wave fitted as standard (Lambda and chip nozzle)
- Wave intermittent operation



## Conveyor

- Belt driven conveyor
- 24V DC drive motor
- Conveyor speed 0 – 2 m/min.

- 1 PCB carrier included
- Adjustable conveyor angle 5-9°
- Conveyor speed shown at digital display



## Controls

- Microprocessor controller (with a 2-line display)
- User friendly operation, multi langual
- Solder pot on/off timer
- Memory of 99 recipes

- o Pin Code reader
- o PC-software

**Distributed via:**

PCI Limited  
 Prime Group Building  
 11/5B, Pusa Road, New Delhi - 110005  
 Tel : +91 11 41888999 ( 30 lines )  
 Fax : +91 11 25755815, 25821623  
 EMAIL : pci@prime-pci.com